DMS 1819 B¹₂, B¹₂K, B2, B2K, B2PF, B2PF

U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

Fo Approved ON No. 44-R1387

MATERIAL SAFETY DATA SHEET

MAY 26 1982

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917) DMS 1819 B2

SECTION	1	
MANUFACTURER'S NAME Essex Chemical Corp.	EMERGENCY TEL (213) 53	EPHONE NO. 7 – 7600
ADDRESS (Number, Street, City, State, and ZIP Code) 19451 Susana Rd., Compton, CA 90221		and the second standard second
CHEMICAL NAME AND SYNONYMS N/A	Pro-Seal 735 Ac	ms celerator/
CHEMICAL FAMILY N/A	MULA N/A	1965 a principal necessaria en en el signi el secución en menor deservirantes de la secución de la constitución de la constituc

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV	RDOUS INGREDIENTS ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS		(Units)	BASE METAL		
catalyst Lead peroxide 55-	60%	*:	ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS 4 4 4 4 4 4 4 4		
OTHERS		7 :			
HAZARDOUS MIXTURE	SOF	OTHER LIC	DUIDS, SOLIDS, OR GASES	%	TLV (Units)
		4			
		· · · · · · · · · · · · · · · · · · ·			
					
				1	

SECTION III - PHYSICAL DATA				
N/A	SPECIFIC GRAVITY (H2O=1)	2.2		
N/A	PERCENT, VOLATILE BY VOLUME (%)	0		
N/A	EVAPORATION RATE (=1)	N/A		
Ni1				
	N/A N/A N/A	N/A SPECIFIC GRAVITY (H ₂ O=1) N/A PERCENT, VOLATILE BY VOLUME (%) N/A EVAPORATION RATE (=1)		

SECTION IV - FIRE AND	XPLOSION HAZARD DAT	ΓΑ			
FLASH POINT (Method used)	FLAMMABLE LIMITS		Uel		
Over 230°F	N/A		J.,		
EXTINGUISHING MEDIA					
Dry chemical, foam, (0. water				
SPECIAL FIRE FIGHTING PROCEDURES 2					
Wear cannister face mask.					
	*				
UNUSUAL FIRE AND EXPLOSION HAZARDS None					
None	*				
		1845.ii			
	₹				

		\			
	₹ _{.40}	\ s	SECTION V	- HEA	ALTH HAZARD DATA
THRESHOLD LIN	AIT VALU	E Unknowi	n		
EFFECTS OF OV	EREXPOS	URE \		224666	a, vomiting and headache.
		11 111)	gesteu-i	iausea	, vomitting and neadache.
EMERGENCY AN	D FIRST	AID PROCED	URES		consult physician
				<u>;</u>	consuit physician
				:	
		···			
			SECTION	IVI - F	REACTIVITY DATA
STABILITY	UNS	UNSTABLE		CONDITIO	NS TO AVOID
	STAI	BLE	х		
INCOMPATABILI	TY (Mater	ials to avoid)	Strong	redu	ucing agents.
HAZARDOUS DE	COMPOSI	TION PRODU	JCTS None		
HAZARDOUS		MAY OCCU			CONDITIONS TO AVOID
POLYMERIZATIO	N	WILL NOT	OCCUR	$+$ \times	
		1		<u> </u>	
STEPS TO BE TA			IAL IS RELE	ASED OR	SPILLED Clean spillage with rags or
waste disposa Waste disp regulation	osal s	should be	in acco	odance	with federal, state and local
				<u>:</u>	
				ECIAL	PROTECTION INFORMATION
RESPIRATORY P					
VENTILATION		DCAL EXHAUST			SPECIAL
	MEC	MECHANICAL (General)			OTHER
PROTECTIVE GL	oves Neop:	rene			EYE PROTECTION Safety goggles.
OTHER PROTECT	TIVE EQL	IPMENT C	overall:	s, apr	
					ECIAL PRECAUTIONS
PRECAUTIONS T	O BE TAI	KEN IN HANI	DLING AND S	TORING	Avoid contact and ingestion.
Store i	n clos	sed con	tainer l	below	80°F.
OTHER PRECAU	TIONS	Yellow	label 1	nateri	ial.
			 		

PAGE (2)

GPO 934-130

Form OSHA-20 Rev. May 72